

LT9611UXC --- Product Brief

Dual-Port MIPI DSI/CSI to HDMI2.0 with Audio

1. Features

● Single/Dual-Port MIPI DSI/CSI Receiver

- Compliant with D-PHY1.2 & DSI1.3 & CSI-2 1.3
- Integrated DSC1.2 decoder (fixed 2 slice, 8bpc only, RGB 4k30 max, YCbCr4:2:2 4k60 max)
- 1/2 configurable ports
- 1 clock lane and 1/2/3/4 configurable data lanes per port
- 80Mbps~2Gbps per data lane
- Programmable receiver equalizer
- 3D support: two ports simultaneously receiving L and R frames or odd-L/even-R alternative pixels
- DSI support both burst mode and non-burst mode
- DSI support video formats:
DSC/CSC disabled: Packed 16/18/24/30/36-bit RGB, Loosely Packed 18-bit RGB, Packed 16/24-bit YCbCr4:2:2, Loosely Packed 20-bit YCbCr4:2:2, Packed 12-bit YCbCr4:2:0
DSC disabled, CSC enabled: Packed 16/18/24/30/36-bit RGB, Loosely Packed 18-bit RGB, Packed 16/24-bit YCbCr4:2:2, Loosely Packed 20-bit YCbCr4:2:2
DSC enabled, CSC disabled: Packed 24-bit RGB, Packed 16-bit YCbCr4:2:2, Packed 12-bit YCbCr4:2:0
DSC/CSC enabled: Packed 24-bit RGB, Packed 16-bit YCbCr4:2:2
- CSI support video formats:
DSC/CSC disabled: RGB565/666/888, YUV422 8/10-bit, Legacy YUV420 8-bit
DSC disabled, CSC enabled: RGB565/666/888, YUV422 8/10-bit
DSC enabled, CSC disabled: RGB888, YUV422 8-bit, Legacy YUV420 8-bit
DSC/CSC enabled: RGB888, YUV422 8-bit

● Digital Audio Input

- I2S interface supporting 2-channel audio, with sample rates of 32~192 kHz and sample sizes of 16~24 bits
- SPDIF interface supporting PCM, Dolby Digital, DTS digital audio at up to 192kHz frame rate
- IEC60958 or IEC61937 compatible

● HDMI2.0 Transmitter

- Compliant with HDMI2.0b, HDMI1.4 and DVI1.0
- Compliant with HDCP2.2 and HDCP1.4
- Data rate up to 6Gbps
- On-die back termination
- Programmable transmitter swing and pre-emphasis
- Support 4k@60Hz
- Supported 3D formats: side-by-side(full)
- Supported video formats:
DSC/CSC disabled: 24/30/36-bit RGB, 16/20/24-bit YCbCr4:2:2, 8-bit YCbCr4:2:0
DSC disabled, CSC enabled: 24-bit RGB/YCbCr4:4:4, 16-bit YCbCr4:2:2
DSC enabled, CSC disabled: 24-bit RGB, 16-bit YCbCr4:2:2, 8-bit YCbCr4:2:0
DSC/CSC enabled: 24-bit RGB/YCbCr4:4:4, 16-bit YCbCr4:2:2

● Miscellaneous

- CSC: RGB <-> YUV444 <-> YUV422, support 8-bit only
- Integrated CEC controller(no command parsing)
- External oscillator
- Integrated microprocessor
- Embedded SPI flash for firmware and HDCP keys
- GPIOs for system controls
- Integrated 100/400kHz I2C slave
- Firmware update through SPI or I2C interface

2. General Description

The LT9611UXC is a high performance MIPI DSI/CSI to HDMI2.0 converter.

The MIPI DSI/CSI input features configurable single-port or dual-port with 1 high-speed clock lane, and 1~4 high-speed data lanes operating at maximum 2Gbps/lane, which can support a total bandwidth of up to 16Gbps. LT9611UXC supports burst mode DSI video data transferring, also supports flexible video data mapping path. Integrated DSC decoder implements up to 1:3 visually lossless decompression which reduces bandwidth requirement for UHD video transport, also power consumption and EMI.

The HDMI2.0 output supports data rate up to 6Gbps which provides sufficient bandwidth for 4k@60Hz video. Also HDCP2.2 is supported for data encryption.

Two digital audio input interfaces are available, I2S and SPDIF. The I2S interface supports 2-ch LPCM and the SPDIF interface supports 2-ch LPCM or compressed audio, both at maximum 192kHz sample rate.

The device is capable of automatic operation which is enabled by an integrated microprocessor that uses an embedded SPI flash for firmware storage. System control is also available through the configuration I2C slave interface.

3. Applications

- STB
- PTV Box




Figure 3.1 Application Diagram

4. Ordering Information

Table 4.1 Ordering Information

Part Number	Product Version	Product Status	Operating Temperature Range	Package	Packing Method	MPQ
LT9611UXC	U2	NRND	-40°C to +85°C	QFN64 (7.5*7.5)	Tray	2600pcs
LT9611UXC	U3	EOL	-40°C to +85°C	QFN64 (7.5*7.5)	Tray	2600pcs
LT9611UXC	U4	MP	-40°C to +85°C	QFN64 (7.5*7.5)	Tray	2600pcs
LT9611UXC-AU	U4	MP	-40°C to +85°C	QFN64 (7.5*7.5)	Tray	2600pcs

NRND: Not Recommended for New Designs.
 EOL: End of Life.
 MP: Mass Production.

Note: The suffix –AU denotes that it is an automotive grade device which is qualified by AEC-Q100 grade 3 testing.

Table 4.2 Product Version Information

Product Version	Information	Note
-----------------	-------------	------

U2	<ol style="list-style-type: none"> 1. Support only single MIPI input port. 2. EoTP required for MIPI RX to improve compatibility. 3. Not support HDCP2.2 encryption for HDMI TX. 4. Data stream disparity error for HDMI TX encoder which affects character error detection in downstream receiver, no impact on data decoding. 5. HDMI2.0 compatibility issue due to fixed SSCP position. 6. Timing issue in some DFT chains. 	
U3	<ol style="list-style-type: none"> 1. Support single/dual MIPI input port. 2. EoTP not required for MIPI RX. 3. Support HDCP2.2 encryption for HDMI TX. 4. Data stream disparity error fixed. 5. Adjustable SSCP position. 6. Timing issue in some DFT chains. 	
U4	<ol style="list-style-type: none"> 1. Support single/dual MIPI input port. 2. EoTP not required for MIPI RX. 3. Support HDCP2.2 encryption for HDMI TX. 4. Data stream disparity error fixed. 5. Adjustable SSCP position. 6. DFT timing issue fixed. 	

LONTIUM CONFIDENTIAL

Copyright © 2018-2022 Lontium Semiconductor Corporation, All rights reserved.

Lontium Semiconductor Proprietary & Confidential

This document and the information it contains belong to Lontium Semiconductor. Any review, use, dissemination, distribution or copying of this document or its information outside the scope of a signed agreement with Lontium is strictly prohibited.

LONTIUM DISCLAIMS ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THOSE OF NONINFRINGEMENT, MERCHANTABILITY, TITLE AND FITNESS FOR A PARTICULAR PURPOSE. CUSTOMERS EXPRESSLY ASSUME THEIR OWN RISK IN RELYING ON THIS DOCUMENT.

LONTIUM PRODUCTS ARE NOT DESIGNED OR INTENDED FOR USE IN LIFE SUPPORT APPLIANCES, DEVICES OR SYSTEMS WHERE A MALFUNCTION OF A LONTIUM DEVICE COULD RESULT IN A PERSONAL INJURY OR LOSS OF LIFE.

Lontium assumes no responsibility for any errors in this document, and makes no commitment to update the information contained herein. Lontium reserves the right to change or discontinue this document and the products it describes at any time, without notice. Other than as set forth in a separate, signed, written agreement, Lontium grants the user of this document no right, title or interest in the document, the information it contains or the intellectual property in embodies.

Trademarks

Lontium™ 龙迅™ and ClearEdge™ is a registered trademark of Lontium Semiconductor. All other brand names, product names, trademarks, and registered trademarks contained herein are the property of their respective owners.

Visit our corporate web page at: www.lontiumsemi.com

Technical support: support@lontium.com

Sales: sales@lontium.com