

# LT8641UX --- Product Brief

## HD-DVI2.0 4-In 1-Out Switch

### 1. Features

- 4 inputs, 1output HD-DVI2.0 links
- HD-DVI 1.4/2.0 compliant
- Supports data rates up to 6.0Gbps
- TX/RX side ODTs and management circuitry
- Integrated HPD switch, DDC switch, and +5V Power indicator switch, greatly lowering the cost and simplifying the manufacturing process
- Source/Sink connection detection for flexible system management
- I2C control supported
- Single 3.3V power supply
- 5V-tolerant DDC interfaces
- Jitter cleaning PLL for better performance
- No external crystal is needed
- Adaptive equalization

### 2. General Description

The Lontium LT8641UX HD-DVI2.0 Switch features a 4:1 switch compliant to HD-DVI2.0/1.4 specification, max 6Gbps

high speed data rate, adaptive equalization RX input and pre-emphasized TX output to support long cable application, no XTAL on board to save BOM cost.

LT8641UX HD-DVI2.0 Switch automatically detect the cable loss, and adaptively optimize the equalization setting. The CDR cleans the input data jitter, make it suitable for long cable and cascade application. It support RX termination resistor calibration to further improve signal integrity.

LT8641UX support DDC/ACDC (Auxiliary and Control Data Channel) compliant to HD-DVI2.0/1.4 specification. The integrated DDC and HPD switches further lower the cost of system manufacture, and simplify the routing on the system board. This package is QFN128 14mmx14mm. It operate from -40°C to +85°C.

### 3. Applications

- Front panel buffer for advanced television (HDTV) sets
- Standalone switcher
- Multiple input displays
- Projectors
- A/V receivers




Figure 3.1 Application Diagram

## 4. Ordering Information

Table 4.1 Ordering Information

Part Number	Product Status	Operating Temperature Range	Package	Packing Method	MPQ
LT8641UX_U5	MP	-40°C to +85°C	QFN128 (14*14)	Tray	1190pcs

MP: Mass Production.

LONTIUM CONFIDENTIAL

Copyright © 2015-2024 Lontium Semiconductor Corporation, All rights reserved.

### **Lontium Semiconductor Proprietary & Confidential**

This document and the information it contains belong to Lontium Semiconductor. Any review, use, dissemination, distribution or copying of this document or its information outside the scope of a signed agreement with Lontium is strictly prohibited.

LONTIUM DISCLAIMS ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THOSE OF NONINFRINGEMENT, MERCHANTABILITY, TITLE AND FITNESS FOR A PARTICULAR PURPOSE. CUSTOMERS EXPRESSLY ASSUME THEIR OWN RISK IN RELYING ON THIS DOCUMENT.

LONTIUM PRODUCTS ARE NOT DESIGNED OR INTENDED FOR USE IN LIFE SUPPORT APPLIANCES, DEVICES OR SYSTEMS WHERE A MALFUNCTION OF A LONTIUM DEVICE COULD RESULT IN A PERSONAL INJURY OR LOSS OF LIFE.

Lontium assumes no responsibility for any errors in this document, and makes no commitment to update the information contained herein. Lontium reserves the right to change or discontinue this document and the products it describes at any time, without notice. Other than as set forth in a separate, signed, written agreement, Lontium grants the user of this document no right, title or interest in the document, the information it contains or the intellectual property in embodies.

### **Trademarks**

Lontium™ 龙迅™ and ClearEdge™ is a registered trademark of Lontium Semiconductor. All other brand names, product names, trademarks, and registered trademarks contained herein are the property of their respective owners.

Visit our corporate web page at: [www.lontiumsemi.com](http://www.lontiumsemi.com)

Technical support: [support@lontium.com](mailto:support@lontium.com)

Sales: [sales@lontium.com](mailto:sales@lontium.com)