

LT7641GX --- Product Brief

HDMI2.1/DP1.4 with Type-C to HDMI2.1 Mixed Switch

1. Features

● HDMI2.1 RX&TX

- Compliant with HDMI2.1, HDMI2.0b, HDMI1.4 and DV11.0
- Data rate up to 12Gbps
- Support HDCP 1.4/2.3
- Support HDCP repeater
- Support RGB 8/10/12 bpc, YCbCr4:4:4/ YCbCr4:2:2/ YCbCr4:2:0 8/10/12 bpc
- Support HDR10
- Support FEC
- Support CEC
- Support VRR
- Integrated EDID shadow (max 512-byte)
- Support ARC RX
- Support EARC RX
- Support lane swap and PN swap

● USB Type-C

- Compliant with VESA DisplayPort Alt Mode on USB Type-C Standard 1.0b
- DP Alt Mode support pin assignment C and E
- Compliant with USB power delivery specification 3.0
- Compliant with USB Type-C cable and connector specification 1.3
- Built-in dual CC logic and PD controller for charger and normal communication
- Data roles supported: UFP and DFP
- Power roles supported: source, sink and DRP
- Support USB Billboard

● DP1.4a/eDP1.4b Receiver

- Compliant with DisplayPort specification 1.4a for 1.62Gbps, 2.7Gbps, 5.4Gbps and 8.1Gbps
- Compliant with Embedded DisplayPort specification version 1.4b
- Support SSC

- Support DisplayPort 1/2/4 lanes
- Support ASSR for eDP
- Support HDCP 1.3/2.3
- Support HDCP repeater
- Support SST mode
- Support RGB 6/8/10/12 bpc, YCbCr4:4:4/YCbCr4:2:2/ YCbCr4:2:0 8/10/12 bpc
- Support HDR10
- Support Adaptive-Sync
- Support Horizontal Blanking Expansion

● Digital Audio Input or Output

- I2S interface supports up to 8-channel audio, with sample rates of 32~192 KHz and sample sizes of 16~24 bits
- TDM interface supports up to 8-channel audio, with sample rates of 32~192 KHz and sample sizes of 16~24 bits
- SPDIF interface supports LPCM, Dolby Digital, DTS digital audio up to 192KHz frame rate
- Compliant with IEC60958 or IEC61937

● Resolution

- HDMI2.1 supports up to 4K@144Hz RGB 8bpc, 8K@30Hz RGB 10bpc or 8K@60Hz DSC pass-through
- DP Receiver supports up to 4K@120Hz RGB 8bpc with reduced blanking, 4K@144Hz YCbCr422 8bit or 8K@30Hz RGB 8bpc with reduced blanking

● OSD

- Support font-based and bit-map OSD
- Support up to two separate OSD windows
- Support non-rectangular display
- Support adjustable transparency
- Support copying windows in 3D mode

● Miscellaneous

- CSC: RGB <-> YCbCr4:4:4 <-> YCbCr4:2:2<-> YCbCr4:2:0

- Integrated 100/400KHz I2C slave
- Integrated microprocessor
- External oscillator 25MHz, +/-50ppm
- Embedded SPI flash for firmware and HDCP keys
- Firmware update through AUX, I2C or USB interface
- Power supply: 3.3V and 1.1V

2. General Description

LT7641GX is a high performance HDMI2.1 or DP1.4a with Type-C to HDMI2.1 and MIPI/LVDS mixed switch chip for Display application.

HDCP RX as the upstream of HDCP repeater, can cooperate with HDCP TX of other chips to realize the repeater function.

For HDMI2.1 input, LT7641GX can be configured as 3/4 lanes. Adaptive equalization makes it suitable for long cable application and the maximum bandwidth up to 48Gbps.

For HDMI2.1 output, LT7641GX can be configured as 3/4 lanes. The maximum bandwidth is up to 48Gbps.

Both HDMI2.1 input and output allow for the highest

resolutions of 8K@30Hz, 4K@144Hz or 8K@60Hz with compression data.

The Type-C/DP1.4a input support data rate up to 8.1Gbps be configured as 1/2/4 lanes. Adaptive equalization makes it suitable for long cable application and the maximum bandwidth is up to 32.4Gbps.

Digital audio output interface is available, including I2S/TDM/SPDIF. Digital audio input interface is available, including I2S/SPDIF.

The device is capable of automatic operation which is enabled by an integrated microprocessor that uses an embedded SPI flash for firmware storage. System control is also available through the configuration I2C slave interface.

3. Applications

- Mixed Switch
- Mobile system
- Display
- Video capture
- Video conferencing




Figure 3.1 Application Diagram

4. Ordering Information

Table 4.1 Ordering Information

Product Name	Part Number	Product Status	Package	Bonding Wire	Grade	Operating Temperature Range	Stack Die Option	Packing Method	MPQ
LT7641GX	LT7641GX_U1Q00CEM	Preview	QFN128 (14*14)Saw	Cu	E	-40°C to +85°C	M	Tray	TBD




Figure 4.1 Part Number Naming Rules

Copyright © 2025 Lontium Semiconductor Corporation, All rights reserved.

Lontium Semiconductor Proprietary & Confidential

This document and the information it contains belong to Lontium Semiconductor. Any review, use, dissemination, distribution or copying of this document or its information outside the scope of a signed agreement with Lontium is strictly prohibited.

LONTIUM DISCLAIMS ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THOSE OF NONINFRINGEMENT, MERCHANTABILITY, TITLE AND FITNESS FOR A PARTICULAR PURPOSE. CUSTOMERS EXPRESSLY ASSUME THEIR OWN RISK IN RELYING ON THIS DOCUMENT.

LONTIUM PRODUCTS ARE NOT DESIGNED OR INTENDED FOR USE IN LIFE SUPPORT APPLIANCES, DEVICES OR SYSTEMS WHERE A MALFUNCTION OF A LONTIUM DEVICE COULD RESULT IN A PERSONAL INJURY OR LOSS OF LIFE.

Lontium assumes no responsibility for any errors in this document, and makes no commitment to update the information contained herein. Lontium reserves the right to change or discontinue this document and the products it describes at any time, without notice. Other than as set forth in a separate, signed, written agreement, Lontium grants the user of this document no right, title or interest in the document, the information it contains or the intellectual property in embodies.

Trademarks

Lontium™ 龙迅™ and ClearEdge™ is a registered trademark of Lontium Semiconductor. All other brand names, product names, trademarks, and registered trademarks contained herein are the property of their respective owners.

Visit our corporate web page at: www.lontiumsemi.com

Technical support: support@lontium.com

Sales: sales@lontium.com